

# ALPHA LITE USER MANUAL BOOK



---

PS SERIES

---

**PS750C**

## **Precautions**

[ WARNING ]

---

**1**

Do not open or disassemble the cover to reduce the risk of electric shock.

---

---

**2**

Please wear safety equipment such as safety helmet during work.

---

---

**3**

Be sure to fix the safety chain on the product when installing and moving.

---

---

**4**

Please install the signs below for people to bypass when install the product on high truss.

---

---

**5**

The work should be done under the direction of approved specialist who is trained in safety and mechanical installations.

---

---

**6**

The brightness and color temperature before and after aging may be different.

---

# Contents

Safety Information .....	1
--------------------------	---

## Fixture Information

Fixture Information .....	3
Fixture Exterior View .....	4
Dimensions .....	5
Technical Specifications .....	6

## Fixture Installation

Power Connection .....	7
DMX Connection .....	8

## LCD Screen Instruction

Unlocking .....	9
Screen Instruction .....	10
Menu Tree .....	11
Main Screen by Mode & Product Information .....	12
DMX Mode .....	13
[Channel Change & Address Setup]	
User Mode .....	14
[Intensity & Color Temperature & Tint Adjust]	
Color Mode .....	15
[RGB & Hue & Saturation & White Adjust]	

## Extra Function

Sleep Mode Function .....	16
RDM Function	
Dimming Speed Setup	
Master Function .....	17
Fixture ID Number Setup .....	18
Device Label Setup	

## Error Information

Temperature Sensor .....	19
Network Connection	

## Extra Information

Cross Fader .....	20
Color Macro	

## Protocols

DMX Protocols .....	21
RDM Protocols .....	24



Product name.


---

# PS750C



---

- ⇒ Mainly used in broadcast studio and stage
  - ⇒ Light texture similar to halogen lamp
  - ⇒ 1CH mode available as halogen lighting
  - ⇒ Excellent light quality, and high-efficiency/high CRI design
  - ⇒ 2500~10000K color temperature control function
  - ⇒ RGB + Amber, Lime, Cyan Full Color LEDs are combined to create a scene for all acting parts and a variety of atmospheres
  - ⇒ Maintain final signal when DMX signal is lost
  - ⇒ Support RDM network communication and various mode setting possible
  - ⇒ Smart touch control method makes it easy and convenient to check all information at a glance
  - ⇒ Long life, reduce maintenance costs and power consumption
-

# Fixture Exterior View



## Dimensions




## Technical Specifications

<b>LED Chip Type</b>	350W CSP LED
<b>Estimated LED Lifetime (hours)</b>	50,000
<b>White Light (K)</b>	2,500~10,000 (VCT) Full RGBALC LED
<b>Full Color Light</b>	Full RGB+Amber+Llme+Cyan (6Color Gamut with Hue and Saturation Control)
<b>Color Rendition (%)</b>	CRI 95~98
<b>Dimming (%)</b>	0~100 (16-bit)
<b>Lens Size (mm/inch)</b>	100 / 3.9
<b>Beam Angle (°)</b>	18~38 / 5~10 / 9~18 / 19 / 36 / 50
<b>Signal Control</b>	5-Pin DMX In and Out
<b>Individual Control</b>	Smart Touch LCD Controller
<b>Supported Protocol</b>	DMX512 / RDM
<b>(Optional) Supported Protocol</b>	DMX512 Wireless / RDM Wireless
<b>Remote Device Management</b>	Supported
<b>Channel Function</b>	Dimming / CCT / Tint / Cross Fader / RGBALC / Color Macro / Strobe
<b>Power Input Voltage</b>	AC 100-240V / 50~60Hz
<b>Power Consumption (W)</b>	250
<b>Ambient Temperature Operation ( °C)</b>	-20~45
<b>Spigot Mounting (mm)</b>	16 / 28
<b>Tilt Angle ( °)</b>	+ / - 90
<b>Body Dimensions (mm/inch) (WHD)</b>	670 x 200 x 185 / 26.4 x 7.9 x 7.3
<b>Full Dimensions with Manual Yoke (mm/inch) (WHD)</b>	745 x 294 x 294 / 29.3 x 11.6 x 11.6
<b>Body Weight (kg/lbs)</b>	5.6 / 12.3
<b>Full Weight with Manual Yoke (kg/lbs)</b>	9.2 / 20.3
<b>Protection Class</b>	IP20

\* This specification data is based on the aging state of the equipment, and the brightness and color temperature before and after aging may be different .

## Power Connection

AC power at 100-240V, 50-60Hz



1 POWER ON/OFF SWITCH

2 POWER IN

3 DMX IN

4 DMX OUT

5 C-TYPE PORT  
(for ADMINISTRATOR ONLY)

※ Do not connect USB without  
administrator's permission.


- ⚠ WARNING**
1. Observe the proper voltage rang.
  2. If power is supplied outside the range, noise may be generated from the SMPS.
  3. If the operating voltage is out of the proper voltage range, SMPS function may be degraded or damaged.

## DMX Connection

3-pin or 5-pin XLR sockets are equipped for DMX input and output, depending on user needs.

Connect the controller to a lighting, or lighting fixture to other lighting fixture. If user uses a standard DMX controller, the DMX output of the controller can connect directly to the DMX input of the first fixture in the DMX chain.

User must use an adapter cable for connect the DMX controller to other XLR output.




- WARNING**
1. Connect the DMX output of the first lighting fixture in DMX chain to the DMX input of the next fixture.
  2. Connect one output to the input of the next fixture until all fixtures are connected.
  3. In the last lighting fixture, the DMX cable must be end with a terminator (120 Ω resistor) in DMX output signal (+, -).

## Unlocking

When the fixture is turned on, the Smart Touch screen automatically locked. To unlock the touch screen, touch the finger icon (A) three times. If you do not touch for 30 seconds, the lock is reset.

### [ Main Screen (Locked) ]




### [ Fixture ID Screen (Locked) ]




## Screen Instructions

### [ Main Screen (Unlocked) ]



### [ Setting Screen ]



01	<b>Current Mode</b>	Display DMX MODE or USER MODE or COLOR MODE.
02	<b>Current Channel Mode</b>	Display current channel mode (only display on DMX MODE)
03	<b>DMX512 Address</b>	Display current DMX512 Address.
04	<b>Brightness (Intensity)</b>	Displays the brightness value(0~100%) of the equipment.
05	<b>CCT (Correlated Color Temperature)</b>	Displays the color temperature(2500~10000K) of the equipment.
06	<b>Fixture Current Temperature</b>	The current temperature of the instrument is detected and displayed in ° C.
07	<b>Activated Function Control Bar</b>	Adjust the selected function among Intensity, Color Temperature and Tint.
08	<b>Home</b>	Return to the main screen
09	<b>DMX512 Mode &amp; Address Setup</b>	Set channel mode and DMX512 address
10	<b>User Mode Setup</b>	Set 'Intensity' and 'CCT' manually
11	<b>Color Mode Setup</b>	Set 'RGB' lighting color, 'Saturation', and 'Intensity'
12	<b>Setting</b>	Setting or changing the function of the equipment.
13	<b>Fixture ID</b>	Displays numbers for equipment management.
14	<b>Equipment Information</b>	Displays the help that describes the screen.
15	<b>Screen Rotation</b>	LCD screen is rotated 180° for each touch.
16	<b>Sleep Mode Setup</b>	Activate and deactivate LCD Auto off function
17	<b>Master Setup</b>	Activate and deactivate Master function
18	<b>RDM Mode Setup</b>	Activate and deactivate RDM function
19	<b>Dimming Speed Setup</b>	Set dimming speed

# Menu Tree

- ⊖ Home [Main screen]
  - ⊖ DMX512 Mode
    - ..... DMX mode select
    - ..... DMX address input
    - ⊖ Information
      - ..... DMX channel value
  - ⊖ User Mode
    - ..... Intensity setup
    - ..... Color temperature setup
    - ..... Tint setup
    - ⊖ Information
      - ..... Description of each function
  - ⊖ Color Mode
    - ..... RGB color setup
    - ..... Saturation setup
    - ..... White setup
    - ⊖ Full screen
      - ..... Individual RGB setup and Preset
    - ⊖ Information
      - ..... RGBW value
  - ⊖ Setting
    - ..... Sleep mode setup
    - ..... Master function setup
    - ..... RDM mode setup
    - ..... Dimming speed setup
    - ⊖ Information
      - ..... Description of each function
  - ⊖ Fixture ID
    - ⊖ Fixture ID screen
      - ..... Fixture ID number input
      - ⊖ Information
        - ..... Description of fixture ID
  - ⊖ Information
    - ..... Basic equipment information
  - ⊖ Rotate

## Main Screen by Mode & Product Information

### 001 Main Screen by Mode Information

HOME

DMX MODE

USER MODE

COLOR MODE

The current mode is displayed in the upper left corner of the main screen among DMX mode, user mode and color mode, and the DMX address number of the equipment is displayed in the middle with a yellow number. At the bottom, the current lighting value and fixture temperature are displayed, and some lighting value can be adjusted on the main screen by touching the value.

#### [ DMX MODE ]



#### [ USER MODE ]



#### [ COLOR MODE ]



### Product Information

HOME

INFO

Product model name, firmware version, UID number, current temperature of equipment, usage time of equipment, LED usage time, website, manual download link, etc. by clicking the INFO button on the main screen.

Each 'MENU' ▶ Touch the 'INFO' ▶ User can check the menu description and functions.



## DMX Mode Channel Change & Address Setup

**DMX MODE** : It is used to adjust value by DMX512 signal.


HOME

DMX512 MODE

Move to the DMX channel change screen.

In DMX512 MODE screen, user can select DMX channel mode on top tap.

▶ Input DMX512 address by pressing the number pad.




DMX512 MODE SCREEN

INFO

Displays each channel information and value.

※ To return to the previous screen, press the 'INFO' button again.



### Information

- 1 (1 Ch Mode) : Dimming
- 3 (3 Ch Mode) : Dimming, CCT
- 5 (5 Ch Mode) : Dimming, CCT, Tint, Cross Fader, Color Macro
- 12 (12 Ch Mode) : Dimming, CCT, Tint, Cross Fader, Red, Green, Blue, Amber, Lime, Cyan, Color Macro, Strobe

\* Support channels and features vary by product.

## User Mode Setup & Intensity / CCT / Tint Adjust

**USER MODE** : It is used when the user directly manipulates the equipment.

HOME

USER MODE

Move to user-operable screen to change Intensity/CCT/Tint.

OR



'Current Intensity'  
'Current CCT'  
'Current Tint'

Activate control bar and adjust value directly according to selected function.

※ In DMX mode, even if you press the current value on the main screen, the bottom bar is not active.

USER MODE screen ▶ Touch the function you want to change ▶ **Active in Orange** ▶ Adjust the value with touch or drag.

Drag the activated bar close to the desired value, and then touch  $\uparrow$ ,  $\downarrow$  to set the exact value.





USER MODE SCREEN

INFO

Displays description of each function.

※ To return to the previous screen, press the 'INFO' button again.



### Information

- Intensity : The number indicates the current brightness value of the fixture and is displayed from 0 to 100%.
- CCT : The number indicates the current color temperature value of the fixture and is displayed from 2,500~10,000Kelvin.
- Tint : The number indicates the current tint(Gamma) value of the fixture and is displayed from -1.00(Magenta) to +1.00(Green).

## Color Mode Setup & RGB / Hue / Saturation / White Adjust

**COLOR MODE** : It is used when the user directly manipulates the equipment.

HOME → COLOR MODE → Move to user-operable screen to change Hue/Saturation

COLOR MODE screen ▶ Touch the function you want to change ▶ Active in Orange ▶ Adjust the value with touch or drag.

- Individual RGB value adjustment and saving preset (#1~9) can be specified through the [ ] button.
- Fine adjustment of RGB values and the number of presets can be changed through the up, down, left and right arrows.

After adjusting the desired value, press 'Enter' ▶ It returns to the COLOR MODE screen.




COLOR MODE SCREEN →

INFO →

Displays description of each function.

※ Press the INFO button again to return to the 'COLOR MODE' screen.



Information

- Color Wheel Gradient : Touch or drag the color user want
- Hue : Drag and select the Hue user want.
- Saturation : The number indicates the current saturation value of the fixture and is displayed from 0 to 100%.
- White : The number indicates the current White LED brightness value of the fixture and is displayed from 0 to 100%.

## Extra Function

### - Sleep Mode / Master / RDM / Dimming Speed

HOME

SETTING

Move to additional settings other than the main icon.

SETTING screen ▶ Touch ON/OFF the function you want to change among SLEEP MODE, MASTER, and RDM MODE ▶ **Active in Orange** ▶ Set ON/OFF

- DIMMING SPEED SETUP can be activated by touching, and press **+**, **-** to adjust the value.




SETTING SCREEN

INFO

Displays description of each function.

※ Press the INFO button again to return to the setting screen.



#### Information

- **Sleep mode setup (Default=Off)** The function to automatically turn off the screen when there is no operation for 30 seconds. If OFF, it is always on the screen while power is on.
- **Master setup (Default=Off)** The function to synchronize and user control all connected fixtures without a console connection. If OFF, the DMX signal will follow.
- **RDM setup (Default=On)** The function to enable two-way wireless communication through RDM equipment. If OFF, it is not detected by RDM equipment.
- **Dimming speed setup** The number indicates the current dimming speed value of the fixture and is displayed from 0 to 40. The higher the value, the slower the dimming speed, and '15' is default speed

## Extra Function

### - Sleep Mode / Master / RDM / Dimming Speed

#### Master Setup

- The master slave function allows to synchronize and control all connected lighting fixtures through the DMX signal without a console connection.
- If a problem occurs in the console or communication line, it is possible to control the brightness and CCT and color with only the lighting fixture.
- Main screen ► Setting ► Touch MASTER SETUP, the function turns on. (2 Touch)
- Functions available with one setting of the first lighting fixture.


#### [ Main Screen ]



#### [ Fixture ID Screen ]



ex



- Remove 'DMX in' cable.
- Set '**Master Enable**'
- Set the same channel mode.
- Operation After setting.

- Connecting 'DMX in & out' cable.
- Set '**Master Disable**'
- Set the same channel mode.
- No operation after setting.

## Fixture ID & Label Setup


HOME

FIXTURE ID

Move to fixture management number setting screen.

Move to input screen that can change the number ► Input the desired number 001 to 9999 and press Enter ► Move to the FIXTURE ID screen that displays the large size entered value ► Touch HOME icon to go back to the main screen.

### [ Main Screen ]



### [ Fixture ID Screen ]




### [ Fixture ID Input Screen ]

Fixture ID  
Input  
Screen

INFO

Displays description of each function.

※ It is the number value 001 to 9999 for the management of the lighting fixture can be changed by manual or RDM device.



### [ Device Label Setup ]



#### [ Change the device label through RDM ]

◁ The device label is basically the model name. It can be changed through RDM communication, but it can't be changed through the Smart Touch LCD ▷

Enter the device name and the management number in the 'Device Label' field. ► The entered contents are displayed in the upper left corner.

- The fixture ID is displayed in 3 or 4 digits from automatically recognized 4 digits in contents.
- If user do not enter any number, the fixture ID is displayed as '001'.

	ex 1	ex 2	ex 3	ex 4	ex 5
<b>Input(Device Label in RDM)</b>	PROFILE123	PROFILE123	PROFILE12345	PROFILE	STUDIO13-23
<b>Fixture Label(in Fixture)</b>	PROFILE123	PROFILE123	PROFILE12345	PROFILE	STUDIO13-23
<b>ID Number(in Fixture)</b>	123	1234	2345	001	023

## Error Information

### Temperature Sensor

Detects the temperature of the current fixture(LED source, housing) and displays it on the Smart Touch LCD screen.



If it exceeds 85°C, the actual LED output will be 0%, and


**“Temperature Error!!”**

**“Please Check Device!!”**

will be displayed.

The error messages are only displayed on the main screen and the fixture ID screen. Even if the temperature falls to the normal range, It does not disappear.

In this case, normalize the temperature of the equipment and restart it.



### Network Connection


When the DMX512 network connection is lost, the DMX512 address number on main screen and the fixture ID screen blinks. Reconnect after checking the connection status.

## Cross Fader & Color Macro

### Cross Fader

#### [In 4 or 7 channel mode]

- When the DMX value of channel 3(Cross Fader) is 0, the set color temperature(CCT) is displayed by channel 2.
- When the DMX value of channel 3 is 255, only Red(channel 4), Green(channel 5), Blue(channel 6) and White(channel 7) color values are displayed.
- As the DMX value of channel 3(Cross Fader) increases, RGB and White values become darker.
- The DMX value of channel 3 adjusts relatively the brightness ratio of channel 2 and channel 4~7.



### Color Macro

Channel 4 is Color Macro express rainbow gradation effect.

The order is


**RED**

>

**GREEN**

>

**BLUE**



## DMX Protocols (1/4) Channel Mode

Mode	Channel	DMX Value	%	Function
<b>1</b>	1	0-255	0-100	Dimmer

Mode	Channel	DMX Value	%	Function
<b>3</b>	1	0-255	0-100	Dimmer
	2	0-255	See DMX Protocols (2)	Color Temperature (CCT)
	3	0-119 / 120-255	See DMX Protocols (3)	Tint

Mode	Channel	DMX Value	%	Function
<b>5</b>	1	0-255	0-100	Dimmer
	2	0-255	See DMX Protocols (2)	Color Temperature (CCT)
	3	0-119 / 120-255	See DMX Protocols (3)	Tint
	4	0-255	0-100	Cross Fader
	5	0-255	See DMX Protocols(4)	Color Macro

Mode	Channel	DMX Value	%	Function
<b>12</b>	1	0-255	0-100	Dimmer
	2	0-255	See DMX Protocols (2)	Color Temperature (CCT)
	3	0-119 / 120-255	See DMX Protocols (3)	Tint
	4	0-255	0-100	Cross Fader
	5	0-255	0-100	Red
	6	0-255	0-100	Green
	7	0-255	0-100	Blue
	8	0-255	0-100	Amber
	9	0-255	0-100	Lime
	10	0-255	0-100	Cyan
	11	0-255	See DMX Protocols (4)	Color Macro
	12	0-255		Strobe

## DMX Protocols (2/4)

### 3 & 5 & 12 Channel Mode : Color Temperature

DMX Value	Function								
0~1	2500	51~52	4000	102~103	5500	153~154	5500	204~205	5500
2~3	2550	53~54	4050	104~105	5550	155~156	5550	206~207	5550
4~5	2600	55~56	4100	106~107	5600	157~158	5600	208~209	5600
6	2650	57	4150	108	5650	159	5650	210	5650
7~8	2700	58~59	4200	109~110	5700	160~161	5700	211~212	5700
9~10	2750	60~61	4250	111~112	5750	162~163	5750	213~214	5750
11	2800	62	4300	113	5800	164	5800	215	5800
12~13	2850	63~64	4350	114~115	5850	165~166	5850	216~217	5850
14~15	2900	65~66	4400	116~117	5900	167~168	5900	218~219	5900
16	2950	67	4450	118	5950	169	5950	220	5950
17~18	3000	68~69	4500	119~120	6000	170~171	6000	221~222	6000
19~20	3050	70~71	4550	121~122	6050	172~173	6050	223~224	6050
21~22	3100	72~73	4600	123~124	6100	174~1v75	6100	225~226	6100
23	3150	74	4650	125	6150	176	6150	227	6150
24~25	3200	75~76	4700	126~127	6200	177~178	6200	228~229	6200
26~27	3250	77~78	4750	128~129	6250	179~180	6250	230~231	6250
28	3300	79	4800	130	6300	181	6300	232	6300
29~30	3350	80~81	4850	131~132	6350	182~183	6350	233~234	6350
31~32	3400	82~83	4900	133~134	6400	184~185	6400	235~236	6400
33	3450	84	4950	135	6450	186	6450	237	6450
34~35	3500	85~86	5000	136~137	6500	187~188	6500	238~239	6500
36~37	3550	87~88	5050	138~139	6550	189~190	6550	240~241	6550
38~39	3600	89~90	5100	140~141	6600	191~192	6600	242~243	6600
40	3650	91	5150	142	6650	193	6650	244	6650
41~42	3700	92~93	5200	143~144	6700	194~195	6700	245~246	6700
43~44	3750	94~95	5250	145~146	6750	196~197	6750	247~248	6750
45	3800	96	5300	147	6800	198	6800	249	6800
46~47	3850	97~98	5350	148~149	6850	199~200	6850	250~251	6850
48~49	3900	99~100	5400	150~151	6900	201~202	6900	252~253	6900
50	3950	101	5450	152	6950	203	6950	254	6950
								255	10000

# DMX Protocols (3/4)

3 & 5 & 12 Channel Mode : Color Macro

DMX Value	Color Value	Color Macro
1 - 6		
7 - 12		
13 - 18		
19 - 24		
25 - 30		
31 - 34		
35 - 38		
39 - 42		
43 - 46		
47 - 50		
51 - 54		
55 - 58		
59 - 62		
63 - 66		
67 - 70		
71 - 74		
75 - 78		
79 - 82		
83 - 86		
87 - 90		
91 - 94		
95 - 98		
99 - 102		
103 - 106		
107 - 110		
111 - 114		
115 - 118		
119 - 122		
123 - 126		
127 - 130		

DMX Value	Color Value	Color Macro
131 - 134		
135 - 138		
139 - 142		
143 - 146		
147 - 150		
151 - 154		
155 - 158		
159 - 162		
163 - 166		
167 - 170		
171 - 174		
175 - 178		
179 - 182		
183 - 186		
187 - 190		
191 - 194		
195 - 198		
199 - 202		
203 - 206		
207 - 210		
211 - 214		
215 - 218		
219 - 222		
223 - 226		
227 - 230		
231 - 234		
235 - 238		
239 - 242		
243 - 246		
247 - 250		
251 - 255		

## DMX Protocols (4/4)

3 & 5 & 12 Channel Mode : Tint / 12 Channel Mode : Strobe

### [ Tint ]

Mode	DMX Value	Output Value	Function
3	0~10	0	No Effect
	11~20	(-)1.00	Full Magenta
	21~119	(-)0.99 ~ (-)0.01	99~1% Magenta
	120~145	0	No Effect
	146~244	(+)0.01 ~ (+)0.99	1~99% Green
	245~255	(+)1.00	Full Green

### [ Strobe ]

DMX Value	Channel
0	Neutral / No effect
1~255	1 / Slow ~ 255 / Fast

## RDM Protocols (1/3)

Parameter ID	Discovery command	SET command	GET command
DISC_UNIQUE_BRANCH	YES		
DISC_MUTE	YES		
DISC_UN_MUTE	YES		
DEVICE_INFO			YES
SUPPORTED_PARAMETERS			YES
SOFTWARE_VERSION_LABEL			YES
DMX_START_ADDRESS		YES	YES
IDENTIFY_DEVICE		YES	YES
DEVICE_MODEL_DESCRIPTION			YES
MANUFACTURER_LABEL			YES
DEVICE_LABEL		YES	YES
SENSOR_DEFINITION			YES
SENSOR_VALUE			YES
DMX_PERSONALITY		YES	YES
DMX_PERSONALITY_DESCRIPTION			YES
STATUS_MESSAGES			YES

## RDM Protocols (2/3)

No	Device Property	Value (Example)	Description	User Setting	Remarks
1	Device Model Description	PS750C	Model number of the device	Disable	
2	Manufacturer Label	ALPHA LITE	Name of the manufacturer	Disable	
3	Device Label	PROFILE123	Fixture name and management number	Enable	ex) Input : PROFILE123 · Name : PROFILE123 · Management # : 123 - Automatic recognition of up to 4 digits. If there is no number, the default is '001'.
4	Software Version Label	M0E-v1.10-v5.27-180928	Software version	Disable	
5	DMX Personality	1 Ch. Mode	DMX channel mode and color temperature setting	Enable	See (Table 1)
6	DMX Start Address	1	DMX address	Enable	1-512 Range
7	Device Hours	N/A		N/A	Display only, no actual response.
8	Lamp Hours	N/A		N/A	Display only, no actual response.
9	Lamp State	N/A		N/A	Display only, no actual response.
10	Lamp On Mode	N/A		N/A	Display only, no actual response.
11	Display Invert	On	LCD screen display direction	Enable	· Off : 0° · On : 180° · Auto : Current opposite direction
12	Identify Device	Off	Selected fixture blinking indication	Enable	· Off : Deactivates blinking · On : Activates blinking
13	Speed Set	15	Dimming delay Setting	Enable	0-40 range The larger the value, the slower the dimming.
14	Display Mode	0	Normal screen / Fixture ID screen transitions	Enable	· 0 : Normal screen · 1 : Fixture ID screen
15	Max. Temp	75	Fixture maximum temperature display	Enable	Use for initialization if necessary

### [ Lamp Controls ]

No	Control Property	Value (Example)	Description	User Setting	Remarks
1	Identify On	N/A	Device identification action active	Enable	Identify device = Same as On
2	Identify Off	N/A	Device identification action inactive	Enable	Identify device = Same as Off
3	Cold Reset	N/A	Device reset(restart)	Enable	Same as Warm reset
4	Warm Reset	N/A	Device reset(restart)	Enable	Same as Cold reset

## RDM Protocols (3/3)

### [ Sensor ]

No	Device Sensors	Value (Example)	Description	User Setting	Remarks
1	Sensor Temp	64°C	Current fixture temperature	Disable	

### [ Error Message ]

No	Condition	Level	Description	Display
1	Sensor Over Temp	Warning	Fixture temperature 46 ~ 69°C	Orange message
2	Sensor Over Temp	Error	Fixture temperature over 70°C	Red message

### [ Table 1 ]

Model	Value	Description
12 Ch. Model Device (Variable Color Temperature & RGB)	1 Ch. Mode	1 Ch. Mode
	3 Ch. Mode	3 Ch. Mode
	5 Ch. Mode	5 Ch. Mode
	12 Ch. Mode	12 Ch. Mode
	1 Ch. 2500K	1 Ch. Mode + 2500K Color Temperature
	1 Ch. 2900K	1 Ch. Mode + 2900K Color Temperature
	1 Ch. 3200K	1 Ch. Mode + 3200K Color Temperature
	1 Ch. 4000K	1 Ch. Mode + 4000K Color Temperature
	1 Ch. 5000K	1 Ch. Mode + 5000K Color Temperature
	1 Ch. 5600K	1 Ch. Mode + 5600K Color Temperature
	1 Ch. 6000K	1 Ch. Mode + 6000K Color Temperature
	1 Ch. 10000K	1 Ch. Mode + 10000K Color Temperature



## ALPHA LITE USER MANUAL BOOK

—

<Tel> 82-2-6317-0464

<Fax> 82-2-2039-0464

<E-mail> [hello@alpha-lite.net](mailto:hello@alpha-lite.net)

<Web> [www.alpha-lite.net](http://www.alpha-lite.net)